



ELECTRONIC TEST:
OPEN/SHORT/INTERMITTENCE: 100%.

P1	PIN OUT	P2
1	BROWN	1
2	RED	2
3	ORANGE	3
4	YELLOW	4
5	GREEN	5
6	BLUE	6
7	PURPLE	7
8	GREY	8
9	BLACK	9
	OD	
	SHELL	SHELL

⑤	TUBE	∅1.0*21 HEAT SHRINK TUBE	2	PCS
④	MOULDED	45P BLACK PVC	18	G
③	MOULDED	LDPE	8	G
②	CONNECTOR	DB9 PIN FEMALE+back nut:SOLDER TYPE* NICKEL PLATED SHELL, BLUE INSULATION	2	PCS
①	CABLE	(28#) 7/0. 12BC*9C+DRAIN WIRE (7/0. 12BC)+AL-FOIL+BLACK PVC, OD: 5.4+10.2MM	4000	MM
NO	NAME	SPECIFICATIONS	Q'TY	UNIT

Ltemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference
Designed by ACHY	Checked by HELEN	Approved by - date Nov.21,2013	File name DB9P F to DB9P F Date Nov.21,2013 Scale FREE
ANGLE:		LYNDAHL®	LKPK020-40
UNIT:MM		LKPK020-40	Edition 1 Sheet 1/1